

GENERAL SPECIFICATIONS

Category	Sub-category
Wood	Light
	Type of product
	PMMA + PVC
Width	Length
122 cm	50 m
Adhesive	Acrylic PSA with air release system
Warranty	6 - 12
Stretchable	Not Stretchable
Resistance to scratch	Average
Pattern direction	Length
Thickness (average by category)	215 - 250 µm
Storage condition (maximum 3 years from delivery)	5° C - 30° C
Installation method	Dry
Installation area	Interior - Exterior
Installation temperature	15° C - 30° C
Installation method (ABBA - ABAB)	ABAB



CERTIFICATIONS

CE Wallcovering (EN15102)	Not required	Color fastness to rubbing (ISO 105-X12) - Assessment according to grey scales	Not tested
REACH	Compliant		
Aldehydes after emission (CMR ISO 16000)	Not tested	Color fastness to shampooing (ISO 18168)	Not tested
Volatile Organic Compounds Testing (EN16516)	Not tested	Color fastness to water (ISO 105-E01)	Not tested
Fire rating (EN13501-1)	D-s1,d0	Liquid absorbency capacity (ISO 9073-6 2000)	Not tested
Wall covering - specification for cork roll (EN13085)	Not required	Liquid wicking rate (ISO 9073-6 2000)	Not tested
IMO/MED Modul B - E	Not tested	Dimensional stability (ISO 3759) - 24h at 50° C - 65% humidity	Not tested
RAIL (ISO 5658 - 2:2006 + A1:2011)	Not tested	Heat and thermal cycle resistance	Not tested
Stain resistance (Tchibo)	Not tested	Color fastness to light	Not tested
Antibacterial properties JIS Z 2081 am. 1 (2012)	Not tested	Adhesion Test	Tested
Spongeability (EN12956)	Not tested	Moisture resistance	Not tested
Washability (EN12956)	Not tested		
Scrubability (EN12956)	Not tested		

CARE AND MAINTENANCE

DURABILITY:
This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, crackling, scaling, delamination).

MAINTENANCE:
Maintaining Exterior Film is crucial for its appearance and longevity. Clean it regularly based on location, pollution, and exposure to natural elements. Hand cleaning is recommended: start by rinsing with clean water to remove loose dirt, then gently wash with a mild detergent with a pH between 5 and 8.5 using a soft cloth or sponge, working from top to bottom. Thoroughly rinse to remove detergent residue and let it dry naturally or dab with a microfiber towel to prevent water spots. Avoid abrasive tools and harsh chemicals. Regularly inspect for damage and address issues promptly. Following these guidelines will keep the film looking its best and extend its lifespan. For façade cleaning or specific information about warranty, refer to the External Guidelines available under Marketing resources on our website.

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.